

Thank you for purchasing the **Ultra-Fab King Pin Tripod**. It was a wise purchase, and I'm sure it will provide you with many years of service.

Assembly instructions

Most of the assembly has been completed for you, however you will need To attach the foot pads, the connecting arms and chain. Nuts and bolts are provided. Where and how you assemble the connecting arms determines the range of use and how well it folds up.

The lower hole range of 42" to 54"

The higher selection has a range of 38.5" to 53.5"

Optional 8" extension legs (part # 19-950002)

When assembling, attach the connecting arms to the same side of each leg. If you attach to the right side of the leg, do the same on the remaining connections. You need to keep the brackets and connections in a straight line for folding purposes.

Tighten all bolts, then back them off by ½ turn. This will allow for the pivoting action required in opening and closing.

- 1) **Connecting arms** (item 3) you should have 3 arms. Attach an arm to each tripod leg, (item 2) use a 1 ¾ bolt.
- 2) Attach **foot pads** (item 9) secure to each tripod leg
- 3) **Connecting bracket**, (item 4) the connecting arms will attach to this bracket, use the 1" truss bolts. Before doing so, slip the bottom link of the chain over the connector bracket (the double thickness side) and then secure.

How to Use

To use your Ultra-Fab King Pin Tripod, hold the chain in one hand, and position the tripod below the king pin of your coach. Pull up on the chain lifting the cup up over the king pin. Hook the chain link over the pin welded to the leg bracket. Turn the handle of the cup counter clockwise until the cup is snug against the king pin. Two or three additional turns are normally sufficient for stabilization.

To lock, place lock through the 2 holes in cup and lock. The neck of the lock has enough interference in the cup, that the king pin cannot be removed.

Your King pin tripod is now stable and secure.

Ultra Fab Products Inc.

19-950001

King Pin Tripod

NO.	QTY.	PART NO.	DESCRIPTION
1	1	19-001006	BRACKET-LEG
2	3	19-001002	LEG
3	3	19-001003	ARM
4	1	19-001004	BRACKET-CONNECTING
5	1	19-001008	CUP-KING PIN
6	1	19-001005	CHAIN
7	1	19-001022	PAD LOCK
8	1	19-001007	HANDLE
9	3	19-001001	FOOTPAD
10	6	19-001019	BOLT-1/2-13 X 1 1/2" HEX
11	3	19-001020	BOLT-1/2-13 X 1 1/2" HEX
12	3	19-001018	BOLT-3/8-16 X 1" TRUSS
13	12	38-020090	NUT-3/8-16 NYLOCK
14	1	19-950002	EXTENSION-8" (OPTIONAL)

